

# FF28LWHMED2



26.63" x 18.5" x 17.75" (H x W x D)

Compact auto defrost medical/scientific all-refrigerator with digital thermostat, NIST calibrated thermometer/alarm, front lock, hospital grade cord, and internal fan

## Highlights:

Specially designed and featured to meet the CDC and VFC's guidelines for safe vaccine storage

User-friendly front control panel keeps the thermostat and alarm in reach without having to open the door

Assembled in the USA from domestic and imported components

## Product Features:

|                                     |  |
|-------------------------------------|--|
| Reliable temperature stability      | Designed and engineered to store vaccines and other sensitive materials under stable temperature conditions  |
| Digital thermostat                  | Digital microprocessor for easy and precise temperature management, with all controls externally located for added convenience   |
| High/low temperature alarm          | Audible alarm sounds if the interior temperature rises or falls out of set range   |
| NIST calibrated temperature display | Alarm includes continuous NIST calibrated display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button  |
| Buffered temperature probe          | Thermometer probe is encased in a glycol-filled bottle and stored in a fixed box on the center shelf. This is the ideal way to produce temperature readings closest to stored contents, as recommended by the CDC and VFC's guidelines |
| Factory installed lock              | Keyed lock for added security, with two keys included  |
| Automatic defrost                   | Reduced maintenance with auto defrost system   |
| Internal fan                        | Fan-forced cooling ensures the unit is evenly cooled from top to bottom  |
| Flat door liner                     | Interior design conforms to CDC guidelines to ensure stable conditions for sensitive materials   |

## FF28LWHMED2 Specifications:

| Overview                   |                    |
|----------------------------|--------------------|
| Height of Cabinet          | 26.63" (68 cm)     |
| Width                      | 18.5" (47 cm)      |
| Depth                      | 17.75" (45 cm)     |
| Depth with door at 90°     | 34.5" (88 cm)      |
| Capacity                   | 2.4 cu.ft. (68 L)  |
| Defrost Type               | Automatic          |
| Door                       | White              |
| Cabinet                    | White              |
| US Electrical Safety       | ETL                |
| Canadian Electrical Safety | ETL-C              |
| Amps                       | 0.7                |
| Voltage/Frequency          | 115 V AC/60 Hz     |
| Weight                     | 45.0 lbs. (20 kg)  |
| Parts & Labor Warranty     | 2 Years            |
| Compressor Warranty        | 5 Years            |
| UPC                        | 761101056456       |
| Refrigerator Features      |                    |
| Door Swing                 | RHD                |
| Reversible                 | Factory Reversible |
| Shelf Type                 | Wire               |
| Shelf Qty                  | 2                  |
| Thermostat Type            | Digital            |
| Fan Type                   | Interior           |
| Refrigerant Type           | R600a              |
| Refrigerant Amount         | 0.7oz.             |
| High Side PSI              | 120.0              |
| Low Side PSI               | 70.0               |
| Level Legs Qty             | 2                  |
| Temperature Range          | 2 to 8°C           |
| Dimensions                 |                    |
| Interior Height            | 20.5" (52 cm)      |
| Interior Width             | 15.5" (39 cm)      |
| Interior Depth             | 13.5" (34 cm)      |
| Compressor Step Height     | 7.75" (20 cm)      |
| Compressor Step Width      | 15.5" (39 cm)      |
| Compressor Step Depth      | 5.5" (14 cm)       |

